

## Subway Single-Fiber Bidirectional 40G OEM



### Overview

The YXF-QP-M85L-01D is a four-channel pluggable LC duplex QSFP+ fiber optic transceiver for 40 Gigabit Ethernet applications. The 40G QSFP BIDI SR optical module uses two 20G channels to achieve 40G transmission. With the use of WDM (Wavelength Division. Single Fiber Bidirectional SFP transceivers use simplex single-mode fiber to double the bandwidth, data rates up to 4G and distances up to 160km. WolonFiber manufactures strictly MSA-compliant 40G QSFP+, 50G SFP56, and 50G QSFP28 optical interconnects optimized for mission-critical telecommunications and campus deployments. LC/UPC. Must be used in pairs with 1G SFP BiDi 1550nm-TX/1310nm-RX. This Generic SFP-1G-BX40-U compatible 1000BASE-BX40-U SFP BiDi module supports 1G bi-directional connectivity using WDM technology. By integrating the 1310nm DFB laser and 1550nm PIN photodiode integrated with a trans-impedance. The QSFP-40G-SR4 module supports link lengths of 100 meters and 150 meters, respectively, on laser-optimized OM3 and OM4 multimode fibers. It primarily enables high-bandwidth 40G optical links over 12-fiber parallel fiber terminated with MPO/MTP multifiber female connectors.

## Article Content

Single-Fiber Bidirectional Transmission using 400G ...

We experimentally evaluate the Rayleigh Back-Scattering power penalty in a single-fiber single-wavelength bidirectional link using coherent digital subcarrier-based transceivers and verify a ...

Fiber-Optic Cabling Connectivity Guide for 40-Gbps Bidirectional and ...

Cabling Options for 40-Gbps Two-Fiber Bidirectional Optics (QSFP-40G-SR-BD) Since the introduction of 40 Gigabit Ethernet with the IEEE 802.3ba standard in 2010, the only multimode solution on the

Custom 40G QSFP+ and 50G SFP56/QSFP28 Modules

This BiDirectional (BDSR) optical module transmits 40Gbps over a single pair of standard multimode fiber via a Duplex LC interface. Eliminating the need for expensive MPO cable upgrades, it provides

QSFP-40G-SR-BD (Single-Fiber-Bidirectional Module)

This document provides an overall description of the CE5800& 6800& 7800& 8800 series switches hardware that versions earlier than V200R020C00, helping you obtain detailed information about

40G QSFP BIDI vs 40G QSFP SR4 vs 40G QSFP UNIV: What Is the

What Is 40G QSFP BIDI SR Optical Transceiver Module The 40GBASE-BiDi SR (Bidirectional Short Reach) module is a type of 40G optical transceiver that utilizes a single pair of

ProductSpecification

Description The 40G-QSFP-SR-BD is a high-performance, four-channel, pluggable QSFP+ transceiver designed for short-range duplex data communication and interconnect applications in 40 Gigabit

QSFP 40G SR BD: 40G QSFP+ BiDi Transceiver Explained

Summary: QSFP-40G-SR-BD is a fiber-saving 40G solution that combines short-reach multimode operation with bidirectional signaling. It sits between traditional SR4 and LR4 modules, offering

40G Fiber Optic Transceiver Cable Ordering Guide FBSG03-WW

It enables high-bandwidth 40G optical links over 12-fiber parallel fiber terminated with MPO/MTP multifiber female connectors. It can also be used in a 4x10G mode for interoperability with 10GBASE

40G BiDi QSFP+: Single-fiber Bidirectional Transmission

The YXF-QP-M85L-01D is a four-channel pluggable LC duplex QSFP+ fiber optic transceiver for 40 Gigabit Ethernet applications. This transceiver is a high-performance module for

25G SFP28 ITEMP bidirectional transceivers extend single fiber reach

Maximize single fiber value with bidirectional (1270nm/1310nm) SFP28 25G signals. Extended signal reach of up to 40km is perfect for use in 5G wireless radio heads  
Industrial

40G QSFP BIDI vs 40G QSFP SR4 vs 40G QSFP UNIV: What Is the

Discover the differences between 40G BIDI SR, 40G SR4, and 40G UNIV modules. Explore their compatibility, transmission modes, and fiber types for optimal performance in your 40G

QSFP-40/100-SRBD QSFP28 40G/100GBASE-SR BiDi

As a single transceiver with these two modes of operation, the Cisco dual-rate BiDi enables data center operators to re-use their existing duplex LC-connectorized

1000BASE-BX SFP 40km Side B | Single Fiber | EDGEOPTIC

Supporting 40km transmission over single-mode fiber at 1550/1310nm wavelengths, this BiDi module delivers 21 dB link budget and multi-rate operation from 100 Mbps to 1.25 Gbps.

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://activa.net.pl>

Email: [sales@activa.net.pl](mailto:sales@activa.net.pl)

Phone: +48 662 748 193

Address: ul. Cybernetyki 7B, 02-677 Warsaw, Poland

This document is for informational purposes only. Specifications subject to change without notice.

